

EQUIPMENT KIT CHECKLIST MARANTZ PMD660 KIT

OPERATION AND SAFETY:



LINE VOLTAGE THRESHOLD

This Solid-State Audio Recorder can provide optional 48V Phantom-power. Do not engage Phantom-power in conjunction with battery-powered microphones! To do so will overload and damage the XLR jack!



FRAGILE HANDLE WITH CARE

This Solid-State Audio Recorder utilizes a 1/8" stereo headphone jack for monitoring recording quality. This connection is extremely delicate! Take care to avoid applying pressure against the jack during operation and storage!

PACKING AND STORAGE:

IMPROPERLY OR MESSILY PACKED KITS WILL RESULT IN A FINE!

Pack the Marantz into its foam recess. Make certain the device has been switched off.

Wrap all Power Cables and the USB A-to-B Cable in a figure-eight pattern, and bind with their velcro strap, fuzzy-side out. The power and USB cable, and AC Adapter component should be stored in their clear-vinyl zipper wallet, and packed in the wallet's corresponding foam recess.

Wrap the XLR Cable in broad, alternating loops, and bind with velcro-strap, fuzzy-side out. Place away from case lid edges. Do not pinch XLR Cable in case lid!

Operating Manual is stored behind lid foam.

PACKING EXAMPLE:



In the event of accident or mishap with this equipment, contact the F&DM Checkout Lab Specialist **IMMEDIATELY**: Phone (831) 459-4062 – Email fdmcheckout@ucsc.edu

IN THE EVENT OF MEDICAL EMERGENCY, DIAL 911.